


## File ceiling

code F1200.827XD/01



### PRODUCT DESCRIPTION

Direct light indoor ceiling lamp made of extruded aluminum 6060, complete with led; color rendering index CRI >90. Professional led 12.8 W modules assembled and wired on extruded aluminum heatsink with high performance reflector, equipped with harmonic steel springs for installation in the profile Tools free; wiring through 5 cables with quick coupling terminal blocks; protocol Dimmable Dali / Touch & Dimm. Lamp with color finish white; in polycarbonate with diffusing film. Degree of protection IP40/IP43.

### PRODUCT SPECS

|                              |                              |
|------------------------------|------------------------------|
| Installation method          | Ceiling surface mounted      |
| Absorbed power               | 12,8 W                       |
| Color temperature            | 2700K                        |
| Color rendering index CRI    | >90                          |
| Optic                        | Microprismatic diffuser      |
| Finishing                    | White                        |
| Luminous flux of the product | 1984 lm                      |
| Luminous efficiency          | 155 lm/W                     |
| MacAdam color tolerance      | 3                            |
| Life time estimate           | 50000h Ta 25° L80 B10        |
| Protocol                     | Dimmable Dali / Touch & Dimm |
| Energy efficiency class      | E                            |
| Weight                       | 2.34 Lbs                     |
| Dimension                    | L22.83"                      |
| IP Grade                     | IP40                         |
| Power supply                 | 220-240V 50-60Hz             |

### WEB PAGE



### ASSEMBLY INSTRUCTIONS

