

## File trimless recessed

code F1106.830P/01



### PRODUCT DESCRIPTION

Direct trimless recessed indoor lamp in extruded aluminum 6060, complete with led; color rendering index CRI >90. Professional led 51.2 W modules assembled and wired on extruded aluminum heatsink with high performance reflector, equipped with harmonic steel springs for installation in the profile Tools free; wiring through 5 cables with quick coupling terminal blocks; protocol On/Off; polycarbonate with diffusing film. Protection rating IP40/IP43.

### PRODUCT SPECS

|                              |                                         |
|------------------------------|-----------------------------------------|
| Installation method          | Trimless recessed                       |
| Absorbed power               | 51,2 W                                  |
| Color temperature            | 3000K                                   |
| Color rendering index CRI    | >90                                     |
| Optic                        | Opal polycarbonate diffuser             |
| Finishing                    | White                                   |
| Luminous flux of the product | 7936 lm                                 |
| Luminous efficiency          | 155 lm/W                                |
| MacAdam color tolerance      | 3                                       |
| Life time estimate           | 50000h Ta 25° L80B10                    |
| Protocol                     | On/Off                                  |
| Energy efficiency class      | E                                       |
| Weight                       | 8.27 Lbs                                |
| Dimension                    | L89.17"                                 |
| Hole size                    | 42XL+2 mm                               |
| IP Grade                     | Inst. Parete Ip40 / Inst. Soffitto Ip43 |
| Power supply                 | 220-240V 50-60Hz                        |

### WEB PAGE



### ASSEMBLY INSTRUCTIONS



## OPTIONAL ACCESSORIES

### Couple of closure heads 40 mm

code LT2480.1



Modular system for direct, diffused and/or accent lighting, consisting of hollow profiles made from 66x40 mm painted or anodised extruded aluminium, with a predefined length or cut to measure, available in the following versions: wall-mounted, ceiling-mounted, suspended, recessed with a super-slim edge trim, just 5 mm wide (61.5 x 40 mm) and trimless recessed. To be integrated with LED linear light sources, battens for T16 fluorescent lamps, projectors with built-in LED source and max 16A 3-circuit track modules for inclusion of projectors. Fluorescent battens, complete with 50/60 Hz 230/240 V electronic power supply, LED batten driver included. To be completed with side end caps with Light Proof system, opal white or microprismatic PC diffusing screen (in accordance with EN 12464-1), closing profiles, with a predefined length or cut to measure, or dark-light aluminium grille with high specular qualities and mounting brackets or suspension cables. IP40 protection rating.

Technical Sheet

