

## File 2 suspension 24W/m

code F2306.830XD/01



### PRODUCT DESCRIPTION

Direct light indoor suspension lamp made of extruded aluminum 6060; complete with led; color rendering index CRI >90. Professional led modules assembled and wired on extruded aluminum heatsink with high performance reflector, equipped with harmonic steel springs for installation in the profile Tools free, wiring through 5 cables with quick-release terminal blocks, protocol Dimmable Dali. Lamp with color finish white, in polycarbonate with diffusing film. Degree of protection IP40/IP43.

### PRODUCT SPECS

|                              |                                         |
|------------------------------|-----------------------------------------|
| Installation method          | Suspension                              |
| Absorbed power               | 26,4 W                                  |
| Color temperature            | 3000K                                   |
| Color rendering index CRI    | >80                                     |
| Optic                        | Microprismatic diffuser                 |
| Finishing                    | White                                   |
| Luminous flux of the product | 3678 lm                                 |
| Luminous efficiency          | 139 lm/W                                |
| Protocol                     | Dimmable Dali                           |
| Energy efficiency class      | D                                       |
| Dimension                    | L89.17"                                 |
| IP Grade                     | Inst. Parete Ip40 / Inst. Soffitto Ip43 |
| Power supply                 | 220-240V 50-60Hz                        |



### FILE2 microprismatic LED



### WEB PAGE



### ASSEMBLY INSTRUCTIONS



