

## File 2 trimless recessed 32W/m

code F2132.930X/01



### PRODUCT DESCRIPTION

Lamp with direct light from built-in shaved; color rendering CRI >90. Professional led modules assembled and wired on extruded aluminum heatsink with high performance reflector; equipped with springs in harmonic steel for installation in the profile Tools free; wiring through 5 cables with quick coupling terminal blocks; protocol On/Off. Lamp with colour finish white; . Degree of protection IP40/IP43.

### PRODUCT SPECS

|                              |                                         |
|------------------------------|-----------------------------------------|
| Installation method          | Trimless recessed                       |
| Absorbed power               | 36 W                                    |
| Color temperature            | 3000K                                   |
| Color rendering index CRI    | 90                                      |
| Optic                        | Microprismatic diffuser                 |
| Finishing                    | White                                   |
| Luminous flux of the product | 5240 lm                                 |
| Luminous efficiency          | 146 lm/W                                |
| Protocol                     | On/Off                                  |
| Energy efficiency class      | D                                       |
| Dimension                    | W44.88"                                 |
| Hole size                    | 82XL+2 mm                               |
| IP Grade                     | Inst. Parete Ip40 / Inst. Soffitto Ip43 |
| Power supply                 | 220-240V 50-60Hz                        |



### FILE2 microprismatic LED



### WEB PAGE



### ASSEMBLY INSTRUCTIONS

