


## BEST FRAME ADJUSTABLE

code BT551.935FN/01



### PRODUCT DESCRIPTION

Adjustable direct light recessed lamp with stop, indoor, circular shape complete with high efficiency COB LED, CRI>90 secondary optics in polycarbonate. Colour body white complete with . Optical body made of die-cast aluminum, passive dissipation with black anodized aluminum heatsink high thermal efficiency. Optical group removable from the ring that is fixed and grouted in plasterboard. Swivelling 360 ° on the vertical and tilting axis of +/-20 ° on the horizontal axis. Degree of protection IP20/23.

### PRODUCT SPECS

|                              |                        |
|------------------------------|------------------------|
| Installation method          | recessed with frame    |
| Absorbed power               | 5 W                    |
| Color temperature            | 3500K                  |
| Color rendering index CRI    | >90                    |
| Optic                        | Flood 24°              |
| Finishing                    | White                  |
| Luminous flux of the product | 665 lm                 |
| Luminous efficiency          | 133 lm/W               |
| MacAdam color tolerance      | 2                      |
| Life time estimate           | 50000h L90 B10 ta 25°C |
| Energy efficiency class      | D                      |
| Weight                       | 1.08 Lbs               |
| Dimension                    | L2.17xH2.99 Ø2.56"     |
| IP Grade                     | IP20                   |
| Protection Class             | Class III appliance    |
| Power supply/Transformer     | Not included           |
| Protocol                     | See power supply       |

### WEB PAGE



