


## BEST FRAME ADJUSTABLE

code BT951.927WB/01



### PRODUCT DESCRIPTION

Adjustable direct light recessed lamp with stop, indoor, circular shape complete with high efficiency COB LED, CRI>90 secondary optics in polycarbonate. Colour body white complete with . Optical body made of die-cast aluminum, passive dissipation with black anodized aluminum heatsink high thermal efficiency. Optical group removable from the ring that is fixed and grouted in plasterboard. Swivelling 360 ° on the vertical and tilting axis of +/-20 ° on the horizontal axis. Degree of protection IP20/23.

### PRODUCT SPECS

|                              |                      |
|------------------------------|----------------------|
| Installation method          | recessed with frame  |
| Absorbed power               | 20 W                 |
| Color temperature            | 2700K                |
| Color rendering index CRI    | >90                  |
| Optic                        | Wide 38°             |
| Finishing                    | White                |
| Luminous flux of the product | 2100 lm              |
| Luminous efficiency          | 105 lm/W             |
| MacAdam color tolerance      | 3                    |
| Life time estimate           | 50000h Ta 25° L80B10 |
| Weight                       | 1.08 Lbs             |
| Dimension                    | L3.74xH5.28 Ø4.13"   |
| IP Grade                     | IP20                 |
| Protection Class             | Class III appliance  |
| Power supply/Transformer     | Not included         |
| Protocol                     | See power supply     |

### WEB PAGE



