


Focus 55 driver included

code FS014.927S/01



PRODUCT DESCRIPTION

Cylindrical projector in extruded aluminium adjustable on the vertical axis of 355° and on the horizontal axis of +/- 90°; equipped with round base; powder coating; with COB technology (Chip on Board) for maximum efficiency; absence of multiple shadows; energy-efficient LEDs with high color rendering; secondary lens in high-transparency pmma; optical units available as accessories with tool-free replacement; possibility of accessories such as honey comb, elliptical lens, asymmetric lens, satin lens. Colour finish white. Driver included. Protection rating IP20.

PRODUCT SPECS

Installation method	Wall surface mounted, Ceiling surface mounted
Absorbed power	12 W
Color temperature	2700K
Color rendering index CRI	>90
Optic	Spot 15°
Finishing	White
Luminous flux of the product	1325 lm
Luminous efficiency	110 lm/W
MacAdam color tolerance	2
Life time estimate	2SCDM 50.000h L90 B10 ta25°
Energy efficiency class	D
Dimension	H6.1 Ø2.17"
IP Grade	IP20
Power supply	220-240V 50-60Hz

WEB PAGE



ASSEMBLY INSTRUCTIONS



OPTIONAL ACCESSORIES

Accessori Lens With Ring Satin lens with rings ø55




code L055S.A/01

uncategorized. Bianco finishing
Warning: Not suitable with halogen lamp

Technical Sheet



Accessori Lens With Ring Elipsoid lens with ring ø55



code L055E.A/01

uncategorized. Bianco finishing
Warning: Not suitable with halogen lamp

Technical Sheet



Accessori Lens With Ring Asymmetric lens with ring ø55




code L055A.A/01

uncategorized. Bianco finishing
Warning: Not suitable with halogen lamp

Technical Sheet



Accessori Lens With Ring Honeycomb louver with ring ø55



code L055R.A/01

uncategorized. Bianco finishing

Technical Sheet



